

NTCQS-1hLM Non-Tracking Tack

Product Data Sheet

Description and Physical Properties

Non-Tracking Tack is an emulsion that is used as a tack coat in conditions where it is important that the tack coat not migrate onto thermoplastic striping, tape, stamped or brick crosswalks, concrete aprons, etc.

Physical Properties

- Boiling Point—Approximately 100°C (212°F)
- Percent Volatiles—None
- Appearance—Brown Liquid
- Flammability—Non-flammable (liquid)
- Weight Per Gallon—8.4 lbs
- Solubility in Water—Dispersable
- Odor—Mild Petroleum Odor

Specifications for Non-Tracking Tack

The specification meets the VDOT performance specification for Non-Tracking Tack Coats.

Handling

Protect the emulsion from freezing.
Avoid overheating the emulsion.
Avoid excessive pumping with high shear pumps, especially if the emulsion is cool.

Storage

Grade	Recommended Maximum Storage Temperature, °F	Application Temperatures (°F)	
		Recommended Range	Maximum Allowable
Non-Tracking Tack	125	165	165

Application

Distributor should be equipped with 00 tips.
Material should be heated no higher than 165°.
Material application rate to be .05 to .075 gallons per square yard.

Transport

Regulatory Information	UN Number	Proper Shipping Name	Class	PG	Label
USDOT					Not Regulated



Quality Emulsion for Every Application

Asphalt Emulsion, Inc. • P. O. Box 38128 • Henrico, VA 23231 • 804.264.2425
Fax 804.264.0219 • Toll Free 877.806.4429
www.asphalt-emulsion.com